

M 265 Alanya [Improved Frankenthal] - 2003 2x PAP 104 Mk5 ROV

Turkey

Type: MCM - Mine Countermeasures Ship

Max Speed: 18 kt

Commissioned: 2003

Length: 54.5 m

Beam: 9.2 m

Draft: 2.6 m

Crew: 41

Displacement: 650 t

Displacement Full: 715 t

Propulsion: 2x MTU 16V 538 TB91 Diesels



Sensors / EW:

- Type 2093 - (J/ZQS-3) VDS, Active Only Sonar, VDS, Active-Only Mine Hunting Variable Depth Sonar [Detection & Classification], Max range: 1.1 km
- Type 1007 - (1988, KH 1007) Radar, Radar, Surface Search & Navigation, Max range: 177.8 km
- DR 2000S - (ARBR-16) ESM, ELINT, Max range: 926 km
- Generic Mechanical Cable Cutter Mine Sweep - (ARBR-16) Mine Sweep, Mechanical Cable Cutter, Mine Sweep, Mechanical Cable Cutter, Max range: 0 km
- Generic Magnetic & Acoustic Mine Sweep - (ARBR-16) Mine Sweep, Magnetic & Acoustic Multi-Influence, Mine Sweep, Magnetic & Acoustic Multi-Influence, Max range: 0 km
- Generic Mine Disposal Diver - (80m depth) Mine Neutralization, Diver-deployed Explosive Charge, Mine Neutralization, Diver-deployed Explosive Charge, Max range: 0 km

Weapons / Loadouts:

- 12.7mm/50 MG Burst [10 rnds] - (Facility/Ship, No Anti-Air Capability) Gun. Surface Max: 1.9 km. Land Max: 1.9 km.
- 30mm/82 Compact OTO-Breda/Mauser Mk30 Burst [20 rnds] - Gun. Air Max: 1.9 km. Surface Max: 2.8 km. Land Max: 2.8 km.
- Barricade Chaff - Decoy (Expendable). Surface Max: 1.9 km.
- Barricade Flare - Decoy (Expendable). Surface Max: 1.9 km.