

AJSH 37 Viggen - 1994, AJS 37 with Recon Camera

Sweden

Type: Attack

Min Speed: 350 kt

Max Speed: 920 kt

Commissioned: 1994

Length: 16.3 m

Wingspan: 10.6 m

Height: 5.9 m

Crew: 1

Empty Weight: 9500 kg

Max Weight: 18000 kg

Max Payload: 3600 kg

Propulsion: 1x RM8A



Sensors / EW: - PS-371/A Recce Mod - Radar, Radar, Air & Surface Search, 3D Medium-Range, Max range: 111.1 km
- SATT - (Viggen) ESM, RWR, Radar Warning Receiver, Max range: 222.2 km

Weapons / Loadouts:

- SKA 24D Camera Pod [600mm EO, Long-Range] - Sensor Pod.
- BOZ-100 [Kapsel B] Chaff/Flare Pod - Sensor Pod.
- U22 [Kapsel A] DECM Pod - Sensor Pod.
- RB 24J Sidewinder [AIM-9P-2/3] - (1979) Guided Weapon. Air Max: 18.5 km.
- Red Baron Recon Pod [IR] - Sensor Pod.
- 1200 liter Drop Tank - Drop Tank.
- 30mm ADEN Mk4 x 2 Burst [60 rnds] - (Aircraft) Gun. Air Max: 1.9 km. Surface Max: 1.9 km. Land Max: 2.8 km.
- M/70 135mm Rocket - (Sweden) Rocket. Surface Max: 3.7 km. Land Max: 3.7 km.
- M/71 Virgo 120kg GPB - Bomb. Surface Max: 1.9 km. Land Max: 1.9 km.
- RB 15F Mk1 - (1990) Guided Weapon. Surface Max: 83.3 km.
- RB 75 Maverick EO [AGM-65B] - (1979) Guided Weapon. Surface Max: 11.1 km. Land Max: 11.1 km.
- 500 liter Drop Tank - Drop Tank.

This remarkable aircraft was developed by Saab in the 1960's to replace the Saab 32 Lansens. The prototype first flew in 1967 and the aircraft started entering service in 1971. The design criteria for the new aircraft included Mach 2 speed at altitude, supersonic flight at low level and outstanding STOL performance. To meet the requirements Saab adopted the then unconventional canard delta configuration. Unlike more recent canard designs the foreplanes on the Viggen are fixed but they do have trailing edge flaps. The Viggen is powered by the P&W JT8D turbofan manufactured under license by Volvo as the RM8.

AJSH 37 Viggen - 1994, AJS 37 with Recon Camera

The aircraft was produced in a number of variants, specifically tailored to Swedish requirements. AJ 37 aircraft are optimized for ground attack with a secondary interceptor role. They feature an Ericsson PS-37/A radar, a digital nav/attack system and a HUD. Conversely the JA 37 models are optimized for interception duties but retain a secondary ground attack role. These carry the Ericsson PS-47/A multimode, Doppler, LD/SD radar, Skyflash and Sidewinder AAMs, new avionics and more powerful RM8B engine. The SF and SH 37 models are reconnaissance models with the SH optimized for maritime recon and with a secondary maritime strike role. The SK 37 is a two seat conversion training variant. Around 100 AJ, SH and SF 37s have been converted to a new multirole AJS standard. This gives the aircraft an expanded weapons range and some new avionics. Sixty JA 37s have undergone a Mid Life Upgrade which sees a modified PS-46/A radar, improved avionics and cockpit displays and AIM-120 compatibility added

Original Author: Daniel Hayes